





Type A Cylindrical



Pre-fitting diameter (mm)		Lengths L (mm) Tolerance js13	Quantity per Bag
d inner Ø Tolerance G7	D outer Ø Tolerance s7		
2 ⁺¹² ₊₂	5 ⁺³¹ ₊₁₉	2 - 3	25
3 ⁺¹² ₊₂	6 ⁺³¹ ₊₁₉	4 - 5 - 6 - 10	25
4 ⁺¹⁶ ₊₄	6 ⁺³¹ ₊₁₉	5 - 8 - 10	25
4 ⁺¹⁶ ₊₄	7 ⁺³⁸ ₊₂₃	4 - 8 - 12	25
4 ⁺¹⁶ ₊₄	8 ⁺³⁸ ₊₂₃	4 - 5 - 6 - 8 - 10 - 12	25
5 ⁺¹⁶ ₊₄	8 ⁺³⁸ ₊₂₃	5 - 8 - 10 - 12 - 15 - 16	25
5 ⁺¹⁶ ₊₄	9 ⁺³⁸ ₊₂₃	4 - 5 - 8	25
5 ⁺¹⁶ ₊₄	10 ⁺³⁸ ₊₂₃	5 - 6 - 8 - 10 - 12 - 15	25
6 ⁺¹⁶ ₊₄	9 ⁺³⁸ ₊₂₃	4 - 6 - 10 - 12 - 16	25
6 ⁺¹⁶ ₊₄	10 ⁺³⁸ ₊₂₃	4 - 5 - 6 - 10 - 12 - 15 - 16	25
6 ⁺¹⁶ ₊₄	12 ⁺⁴⁶ ₊₂₈	5 - 6 - 8 - 10 - 12 - 15 - 16	25
7 ⁺²⁰ ₊₅	10 ⁺³⁸ ₊₂₃	5 - 8 - 10	25
8 ⁺²⁰ ₊₅	10 ⁺³⁸ ₊₂₃	6 - 10 - 15	25
8 ⁺²⁰ ₊₅	11 ⁺⁴⁶ ₊₂₈	6 - 8 - 12 - 16 - 20	25
8 ⁺²⁰ ₊₅	12 ⁺⁴⁶ ₊₂₈	6 - 8 - 10 - 12 - 15 - 16 - 20	25
8 ⁺²⁰ ₊₅	14 ⁺⁴⁶ ₊₂₈	8 - 10 - 12 - 15 - 16 - 20	25
9 ⁺²⁰ ₊₅	12 ⁺⁴⁶ ₊₂₈	6 - 10 - 14	25
9 ⁺²⁰ ₊₅	14 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 20	25
10 ⁺²⁰ ₊₅	13 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 16 - 20 - 25	25
10 ⁺²⁰ ₊₅	14 ⁺⁴⁶ ₊₂₈	8 - 10 - 16 - 20 - 25	25
10 ⁺²⁰ ₊₅	15 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 16 - 20 - 25	10
10 ⁺²⁰ ₊₅	16 ⁺⁴⁶ ₊₂₈	8 - 10 - 12 - 15 - 16 - 20 - 25	10
10 ⁺²⁰ ₊₅	18 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 20 - 25	10
12 ⁺²⁴ ₊₆	14 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 20	10
12 ⁺²⁴ ₊₆	15 ⁺⁴⁶ ₊₂₈	10 - 12 - 15 - 16 - 20 - 25	10
12 ⁺²⁴ ₊₆	16 ⁺⁴⁶ ₊₂₈	8 - 10 - 12 - 15 - 16 - 20 - 25	10
12 ⁺²⁴ ₊₆	17 ⁺⁴⁶ ₊₂₈	12 - 15 - 16 - 20 - 25	10
12 ⁺²⁴ ₊₆	18 ⁺⁴⁶ ₊₂₈	8 - 10 - 12 - 15 - 16 - 20 - 25 - 30	10
12 ⁺²⁴ ₊₆	20 ⁺⁵⁶ ₊₃₅	12 - 15 - 20 - 25 - 30	10
14 ⁺²⁴ ₊₆	18 ⁺⁴⁶ ₊₂₈	10 - 14 - 15 - 18 - 20 - 22 - 25 - 28	10
14 ⁺²⁴ ₊₆	20 ⁺⁵⁶ ₊₃₅	10 - 12 - 14 - 15 - 18 - 20 - 22 - 25 - 28 - 30	10
14 ⁺²⁴ ₊₆	22 ⁺⁵⁶ ₊₃₅	15 - 20 - 25 - 30	10
15 ⁺²⁴ ₊₆	18 ⁺⁴⁶ ₊₂₈	15 - 20 - 25 - 30	10
15 ⁺²⁴ ₊₆	19 ⁺⁵⁶ ₊₃₅	10 - 15 - 16 - 20 - 25 - 32	10
15 ⁺²⁴ ₊₆	20 ⁺⁵⁶ ₊₃₅	10 - 12 - 15 - 20 - 25 - 30	10
15 ⁺²⁴ ₊₆	21 ⁺⁵⁶ ₊₃₅	10 - 15 - 16 - 20 - 25 - 32	10
15 ⁺²⁴ ₊₆	22 ⁺⁵⁶ ₊₃₅	15 - 16 - 20 - 25 - 30	10
16 ⁺²⁴ ₊₆	20 ⁺⁵⁶ ₊₃₅	12 - 15 - 16 - 20 - 25 - 30 - 32	10
16 ⁺²⁴ ₊₆	22 ⁺⁵⁶ ₊₃₅	12 - 15 - 16 - 20 - 25 - 30 - 32 - 35	10
17 ⁺²⁴ ₊₆	22 ⁺⁵⁶ ₊₃₅	15 - 20 - 25 - 30 - 35	10
18 ⁺²⁴ ₊₆	22 ⁺⁵⁶ ₊₃₅	12 - 15 - 18 - 20 - 22 - 25 - 28 - 30 - 36	10
18 ⁺²⁴ ₊₆	24 ⁺⁵⁶ ₊₃₅	12 - 18 - 22 - 28 - 30 - 36	10
18 ⁺²⁴ ₊₆	25 ⁺⁵⁶ ₊₃₅	16 - 18 - 20 - 22 - 25 - 28 - 30 - 35 - 36	10
20 ⁺²⁸ ₊₇	24 ⁺⁵⁶ ₊₃₅	16 - 20 - 25 - 32	10
20 ⁺²⁸ ₊₇	25 ⁺⁵⁶ ₊₃₅	15 - 16 - 20 - 25 - 30 - 32 - 35	10
20 ⁺²⁸ ₊₇	26 ⁺⁵⁶ ₊₃₅	15 - 16 - 20 - 25 - 30 - 32 - 35 - 40	10
20 ⁺²⁸ ₊₇	27 ⁺⁵⁶ ₊₃₅	16 - 20 - 25 - 32	10



Type A Cylindrical



Pre-fitting diameter (mm)		Lengths L (mm) Tolerance js13	Quantity per Bag
d inner Ø Tolerance G7	D outer Ø Tolerance s7		
20 ⁺²⁸ ₊₇	28 ⁺⁵⁶ ₊₃₅	16 - 20 - 25 - 30 - 32 - 35 - 40	10
20 ⁺²⁸ ₊₇	30 ⁺⁵⁶ ₊₃₅	20 - 25 - 30 - 35 - 40	10
22 ⁺²⁸ ₊₇	27 ⁺⁵⁶ ₊₃₅	15 - 18 - 20 - 22 - 25 - 28 - 30 - 35 - 36 - 40	10
22 ⁺²⁸ ₊₇	28 ⁺⁵⁶ ₊₃₅	18 - 20 - 22 - 25 - 28 - 30 - 35 - 36 - 40	10
22 ⁺²⁸ ₊₇	29 ⁺⁵⁶ ₊₃₅	18 - 22 - 28 - 36	10
25 ⁺²⁸ ₊₇	30 ⁺⁵⁶ ₊₃₅	20 - 25 - 30 - 32 - 35 - 40	10
25 ⁺²⁸ ₊₇	32 ⁺⁶⁸ ₊₄₃	20 - 25 - 30 - 32 - 35 - 40 - 45	10
25 ⁺²⁸ ₊₇	35 ⁺⁶⁸ ₊₄₃	25 - 30 - 35 - 40 - 45 - 50	5
28 ⁺²⁸ ₊₇	32 ⁺⁶⁸ ₊₄₃	20 - 22 - 25 - 28 - 32 - 36 - 40	5
28 ⁺²⁸ ₊₇	33 ⁺⁶⁸ ₊₄₃	20 - 22 - 25 - 28 - 32 - 36 - 40 - 45	5
28 ⁺²⁸ ₊₇	35 ⁺⁶⁸ ₊₄₃	25 - 30 - 35 - 40 - 45 - 50	5
28 ⁺²⁸ ₊₇	36 ⁺⁶⁸ ₊₄₃	22 - 28 - 36 - 45	5
30 ⁺²⁸ ₊₇	35 ⁺⁶⁸ ₊₄₃	20 - 25 - 30 - 35 - 40 - 45 - 50	5
30 ⁺²⁸ ₊₇	38 ⁺⁶⁸ ₊₄₃	20 - 24 - 25 - 30 - 35 - 38 - 40 - 45 - 50	5
30 ⁺²⁸ ₊₇	40 ⁺⁶⁸ ₊₄₃	20 - 25 - 30 - 35 - 40 - 45 - 50	5
32 ⁺³⁴ ₊₉	38 ⁺⁶⁸ ₊₄₃	20 - 25 - 32 - 40 - 50	5
32 ⁺³⁴ ₊₉	40 ⁺⁶⁸ ₊₄₃	20 - 25 - 30 - 32 - 35 - 40 - 45 - 50	5
35 ⁺³⁴ ₊₉	40 ⁺⁶⁸ ₊₄₃	20 - 25 - 30 - 35 - 40 - 45 - 50	5
35 ⁺³⁴ ₊₉	41 ⁺⁶⁸ ₊₄₃	25 - 35 - 40	5
35 ⁺³⁴ ₊₉	44 ⁺⁶⁸ ₊₄₃	22 - 28 - 35	5
35 ⁺³⁴ ₊₉	45 ⁺⁶⁸ ₊₄₃	25 - 30 - 35 - 40 - 45 - 50 - 60	5
36 ⁺³⁴ ₊₉	42 ⁺⁶⁸ ₊₄₃	22 - 28 - 36 - 45	5
36 ⁺³⁴ ₊₉	45 ⁺⁶⁸ ₊₄₃	22 - 28 - 36 - 45	5
38 ⁺³⁴ ₊₉	44 ⁺⁶⁸ ₊₄₃	25 - 35 - 45	5
40 ⁺³⁴ ₊₉	45 ⁺⁶⁸ ₊₄₃	35 - 40 - 45 - 50	5
40 ⁺³⁴ ₊₉	46 ⁺⁶⁸ ₊₄₃	25 - 30 - 32 - 40 - 50	5
40 ⁺³⁴ ₊₉	50 ⁺⁶⁸ ₊₄₃	25 - 32 - 40 - 45 - 50 - 60	5
45 ⁺³⁴ ₊₉	51 ⁺⁸³ ₊₅₃	28 - 36 - 45 - 56	5
45 ⁺³⁴ ₊₉	55 ⁺⁸³ ₊₅₃	30 - 35 - 40 - 45 - 50 - 55 - 60	5
45 ⁺³⁴ ₊₉	56 ⁺⁸³ ₊₅₃	28 - 36 - 45 - 56	5
45 ⁺³⁴ ₊₉	60 ⁺⁸³ ₊₅₃	40 - 45 - 50 - 60	2
50 ⁺³⁴ ₊₉	56 ⁺⁸³ ₊₅₃	32 - 40 - 50 - 63	2
50 ⁺³⁴ ₊₉	60 ⁺⁸³ ₊₅₃	32 - 40 - 45 - 50 - 60	2
55 ⁺⁴⁰ ₊₁₀	65 ⁺⁸³ ₊₅₃	40 - 55 - 70	2
60 ⁺⁴⁰ ₊₁₀	70 ⁺⁸⁹ ₊₅₉	50 - 60 - 90 - 120	2
60 ⁺⁴⁰ ₊₁₀	72 ⁺⁸⁹ ₊₅₉	50 - 60 - 70	1
60 ⁺⁴⁰ ₊₁₀	80 ⁺⁸⁹ ₊₅₉	90 - 120	1
63 ⁺⁴⁰ ₊₁₀	70 ⁺⁸⁹ ₊₅₉	40 - 50	1
70 ⁺⁴⁰ ₊₁₀	80 ⁺⁸⁹ ₊₅₉	90 - 120	1
80 ⁺⁶⁶ ₊₁₂	(G8) 100 ⁺¹²⁵ ₊₇₁ (s8)	80 - 120	1
100 ⁺⁶⁶ ₊₁₂	(G8) 120 ⁺¹⁶³ ₊₇₉ (s8)	80 - 120	1


Selfoil® HIGH PERFORMANCE

Tolerance in µm / Run-out: IT-9 for D≤50 and IT-10 for D>50






Type B Flanged



Pre-fitting diameter (mm)		D'= Ø Flange (mm)	Thickness e= (mm)	Lengths L (mm) Tolerance js13	Quantity per Bag	
d inner Ø Tolerance G8	D outer Ø Tolerance s8					
3 ^{+16 +2}	6 ^{+37 +19}	9	1,5	4 - 5 - 6 - 10	25	
4 ^{+22 +4}	8 ^{+45 +23}	12	2	4 - 5 - 8 - 10 - 12	25	
6 ^{+22 +4}	10 ^{+45 +23}	14	2	6 - 10 - 15 - 16	25	
8 ^{+27 +5}	12 ^{+55 +28}	16	2	8 - 10 - 12 - 15 - 16	25	
9 ^{+27 +5}	14 ^{+55 +28}	19	2,5	6 - 10 - 14	10	
10 ^{+27 +5}	13 ^{+55 +28}	16	1,5	10 - 16 - 20	10	
10 ^{+27 +5}	14 ^{+55 +28}	18	2	10 - 15 - 20	10	
10 ^{+27 +5}	15 ^{+55 +28}	20	3	10 - 15 - 16 - 20	10	
10 ^{+27 +5}	16 ^{+55 +28}	22	3	8 - 10 - 16	10	
12 ^{+33 +6}	15 ^{+55 +28}	18	1,5	12 - 16 - 20	10	
12 ^{+33 +6}	17 ^{+55 +28}	22	3	10 - 12 - 15 - 16 - 20 - 25	10	
12 ^{+33 +6}	18 ^{+55 +28}	24	3	8 - 12 - 20	10	
14 ^{+33 +6}	18 ^{+55 +28}	22	2	14 - 18 - 22	10	
14 ^{+33 +6}	20 ^{+68 +35}	25	3	14 - 15 - 18 - 20 - 22 - 25 - 28 - 30	10	
15 ^{+33 +6}	19 ^{+68 +35}	23	2	16 - 20 - 25	10	
15 ^{+33 +6}	20 ^{+68 +35}	25	3	15 - 20 - 25 - 30	10	
15 ^{+33 +6}	21 ^{+68 +35}	27	3	16 - 20 - 25 - 32	10	
16 ^{+33 +6}	20 ^{+68 +35}	24	2	16 - 20 - 25	10	
16 ^{+33 +6}	22 ^{+68 +35}	28	3	15 - 16 - 20 - 25 - 30 - 32	10	
18 ^{+33 +6}	22 ^{+68 +35}	26	2	18 - 22 - 28	10	
18 ^{+33 +6}	24 ^{+68 +35}	30	3	18 - 22 - 28	10	
18 ^{+33 +6}	25 ^{+68 +35}	32	4	20 - 25 - 30 - 35	10	
20 ^{+40 +7}	24 ^{+68 +35}	28	2	10 - 16 - 20 - 25	10	
20 ^{+40 +7}	26 ^{+68 +35}	32	3	15 - 16 - 20 - 25 - 30 - 32	10	
20 ^{+40 +7}	28 ^{+68 +35}	35	4	20 - 25 - 30 - 35	10	
22 ^{+40 +7}	27 ^{+68 +35}	32	2,5	18 - 22 - 28	10	
22 ^{+40 +7}	28 ^{+68 +35}	33	4	15 - 20 - 25 - 30 - 35 - 40	10	
22 ^{+40 +7}	29 ^{+68 +35}	36	3,5	18 - 22 - 28 - 36	10	
25 ^{+40 +7}	30 ^{+68 +35}	35	2,5	20 - 25 - 32	10	
25 ^{+40 +7}	32 ^{+82 +43}	40	4	20 - 25 - 30 - 32 - 35 - 40	10	
25 ^{+40 +7}	35 ^{+82 +43}	45	5	16 - 25 - 30	10	
28 ^{+40 +7}	33 ^{+82 +43}	38	2,5	22 - 28 - 36	10	
28 ^{+40 +7}	36 ^{+82 +43}	44	4	22 - 25 - 28 - 30 - 35 - 36 - 40	10	
Selfoil® HIGH PERFORMANCE	30 ^{+40 +7}	38 ^{+82 +43}	46	4	20 - 25 - 30	10
	30 ^{+40 +7}	40 ^{+82 +43}	48	4	25 - 30 - 35 - 40	10
	32 ^{+48 +9}	38 ^{+82 +43}	44	3	20 - 25 - 32	10
	32 ^{+48 +9}	40 ^{+82 +43}	48	4	20 - 25 - 30 - 32 - 35 - 40	10
	35 ^{+48 +9}	45 ^{+82 +43}	55	5	20 - 25 - 30 - 35 - 40	10
	36 ^{+48 +9}	42 ^{+82 +43}	48	3	22 - 28 - 36	10
	36 ^{+48 +9}	45 ^{+82 +43}	54	4,5	22 - 28 - 36	10
	40 ^{+48 +9}	46 ^{+82 +43}	52	3	25 - 32 - 40	5
	40 ^{+48 +9}	50 ^{+82 +43}	60	5	25 - 30 - 32 - 35 - 40	5
	45 ^{+48 +9}	51 ^{+99 +53}	57	3	28 - 36 - 45	5
	45 ^{+48 +9}	56 ^{+99 +53}	67	5,5	28 - 36 - 45	5
	50 ^{+48 +9}	56 ^{+99 +53}	62	3	32 - 40 - 50	5
50 ^{+48 +9}	60 ^{+99 +53}	70	5	32 - 40 - 50	5	
60 ^{+56 +10}	70 ^{+105 +59}	80	5	50 - 60	5	


Tolerance in µm / Run-out: IT-9 for D≤50 and IT-10 for D>50





Type C Spherical

d inner Ø (mm) Tolerance H7	E sphere (mm) Tolerance $\pm 0,05$	Lengths L (mm) Tolerance $\pm 0,15$	Quantity per Bag
4	10	8	25
5	12	9	25
6	14	11	25
7	16	12	25
8	18	13	25
9	20	14.5	25
10	22	16	25
12	23	16	25




Type A Cylindrical

DIMENSIONS IN INCHES

Pre-fitting diameter		Lengths L Tolerance js13	Quantity per Bag
d inner Ø Tolerance G7	D outer Ø Tolerance s7		
1/4"	1/2"	1/4" - 3/8" - 1/2" - 5/8" - 3/4"	25
3/8"	5/8"	3/8" - 1/2" - 5/8" - 3/4" - 1"	25
1/2"	11/16"	1/2" - 5/8" - 3/4" - 1" - 1 1/4"	10
1/2"	3/4"	1/2" - 5/8" - 3/4" - 1" - 1 1/4"	10
5/8"	3/4"	1/2" - 5/8" - 3/4" - 1" - 1 1/4"	10
5/8"	7/8"	1/2" - 5/8" - 3/4" - 1" - 1 1/4"	10
3/4"	7/8"	5/8" - 3/4" - 7/8" - 1" - 1 1/4"	10
3/4"	1"	5/8" - 3/4" - 7/8" - 1" - 1 1/4"	10
3/4"	1 1/4"	5/8" - 3/4" - 7/8" - 1" - 1 1/4"	10
1"	1 1/8"	3/4" - 1" - 1 1/4" - 1 1/2"	10
1"	1 1/2"	3/4" - 1" - 1 1/4" - 1 1/2" - 2"	5
1 1/2"	2"	1 1/2" - 2" - 2 1/4" - 2 1/2"	5
2"	2 1/2"	1 1/2" - 2" - 2 1/4" - 2 1/2"	2
2 1/2"	3"	1 1/2" - 2" - 2 1/4" - 2 1/2"	1



Type AF Cylindrical




Pre-fitting diameter (mm)		Lengths L (mm) Tolerance js13	Quantity per Bag	
d inner Ø _{Tolerance G7}	D outer Ø _{Tolerance s7}			
3 ^{+12 +2}	6 ^{+31 +19}	4 - 10	25	
4 ^{+16 +4}	8 ^{+38 +23}	8	25	
6 ^{+16 +4}	9 ^{+38 +23}	6 - 10 - 12 - 16	25	
6 ^{+16 +4}	10 ^{+38 +23}	6 - 10 - 16	25	
6 ^{+16 +4}	12 ^{+46 +28}	6	25	
8 ^{+20 +5}	11 ^{+46 +28}	8 - 12 - 16	25	
8 ^{+20 +5}	12 ^{+46 +28}	8 - 12 - 16 - 20	25	
10 ^{+20 +5}	13 ^{+46 +28}	10 - 20 - 25	25	
10 ^{+20 +5}	14 ^{+46 +28}	10 - 16 - 20	25	
10 ^{+20 +5}	15 ^{+46 +28}	10	10	
12 ^{+24 +6}	15 ^{+46 +28}	12 - 16 - 20	10	
12 ^{+24 +6}	16 ^{+46 +28}	12 - 16 - 20 - 25	10	
12 ^{+24 +6}	17 ^{+46 +28}	12	10	
14 ^{+24 +6}	18 ^{+46 +28}	14 - 22	10	
14 ^{+24 +6}	20 ^{+56 +35}	14 - 28	10	
15 ^{+24 +6}	19 ^{+56 +35}	16 - 20	10	
16 ^{+24 +6}	20 ^{+56 +35}	16 - 20 - 25 - 32	10	
16 ^{+24 +6}	22 ^{+56 +35}	16 - 20 - 25	10	
18 ^{+24 +6}	22 ^{+56 +35}	18 - 22	10	
18 ^{+24 +6}	24 ^{+56 +35}	22	10	
20 ^{+28 +7}	24 ^{+56 +35}	16 - 20 - 25 - 32	10	
20 ^{+28 +7}	26 ^{+56 +35}	16 - 20 - 25 - 32	10	
22 ^{+28 +7}	27 ^{+56 +35}	18 - 22	10	
25 ^{+28 +7}	30 ^{+56 +35}	20 - 25 - 32	10	
25 ^{+28 +7}	32 ^{+68 +43}	20 - 25 - 32	10	
Selfoil™ HIGH PERFORMANCE	30 ^{+28 +7}	38 ^{+68 +43}	24 - 30 - 38	5
	32 ^{+34 +9}	38 ^{+68 +43}	32	5
	35 ^{+34 +9}	44 ^{+68 +43}	22 - 28 - 35	5
	36 ^{+34 +9}	42 ^{+68 +43}	22	5
	40 ^{+34 +9}	46 ^{+68 +43}	25 - 32 - 40	5
	40 ^{+34 +9}	50 ^{+68 +43}	25 - 32 - 40 - 50	5
	45 ^{+34 +9}	51 ^{+83 +53}	28 - 45	5
	45 ^{+34 +9}	55 ^{+83 +53}	35	5
	45 ^{+34 +9}	56 ^{+83 +53}	36	5
	50 ^{+34 +9}	56 ^{+83 +53}	32	2
	50 ^{+34 +9}	60 ^{+83 +53}	32 - 50	2
	60 ^{+40 +10}	70 ^{+89 +59}	60 - 90	2
	70 ^{+40 +10}	80 ^{+89 +59}	120	1
	80 ^{+66 +12} (G8)	100 ^{+125 +71} (s8)	120	1
	100 ^{+66 +12} (G8)	120 ^{+163 +79} (s8)	120	1

Tolerance in µm / Run-out: IT-9 for D≤50 and IT-10 for D>50



Type BF Flanged



Pre-fitting diameter (mm)		D'= Ø Flange (mm)	e= Thickness (mm)	Lengths L (mm) Tolerance js13	Quantity per Bag
d inner Ø Tolerance G8	D outer Ø Tolerance s8				
3 ⁺¹⁶ ₋₂	6 ⁺³⁷ ₊₁₉	9	1.5	4	25
6 ⁺²² ₋₄	10 ⁺⁴⁵ ₊₂₃	14	2	6 - 10 - 16	25
8 ⁺²⁷ ₋₅	12 ⁺⁵⁵ ₊₂₈	16	2	8 - 12 - 16	25
10 ⁺²⁷ ₋₅	13 ⁺⁵⁵ ₊₂₈	16	1.5	10 - 16	10
10 ⁺²⁷ ₋₅	15 ⁺⁵⁵ ₊₂₈	20	2.5	10 - 16 - 20	10
12 ⁺³³ ₋₆	15 ⁺⁵⁵ ₊₂₈	18	1.5	12 - 16 - 20	10
12 ⁺³³ ₋₆	17 ⁺⁵⁵ ₊₂₈	22	2.5	12 - 16	10
14 ⁺³³ ₋₆	18 ⁺⁵⁵ ₊₂₈	22	2	14 - 18 - 22	10
16 ⁺³³ ₋₆	20 ⁺⁶⁸ ₊₃₅	24	2	16 - 20	10
16 ⁺³³ ₋₆	22 ⁺⁶⁸ ₊₃₅	28	3	16 - 20 - 25	10
18 ⁺³³ ₋₆	24 ⁺⁶⁸ ₊₃₅	30	3	18 - 22	10
20 ⁺⁴⁰ ₋₇	24 ⁺⁶⁸ ₊₃₅	28	2	16 - 20 - 25	10
20 ⁺⁴⁰ ₋₇	26 ⁺⁶⁸ ₊₃₅	32	3	16 - 20 - 25	10
22 ⁺⁴⁰ ₋₇	29 ⁺⁶⁸ ₊₃₅	36	3.5	18 - 22 - 28 - 36	10
25 ⁺⁴⁰ ₋₇	30 ⁺⁶⁸ ₊₃₅	35	2.5	20 - 32	10
25 ⁺⁴⁰ ₋₇	32 ⁺⁸² ₊₄₃	39	3.5	25 - 32	10
Selfoil® HIGH PERFORMANCE	30 ⁺⁴⁰ ₋₇	46	4	30	10
	32 ⁺⁴⁸ ₋₉	48	4	20 - 32	10
	36 ⁺⁴⁸ ₋₉	54	4.5	22 - 36	10
	40 ⁺⁴⁸ ₋₉	60	5	25 - 32 - 40	5
	50 ⁺⁴⁸ ₋₉	70	5	50	5
	60 ⁺⁵⁶ ₋₁₀	80	5	60	5

Tolerance in µm / Run-out: IT-9 for D≤50 and IT-10 for D>50